

FIRE

EXTINGUISHER



Multi-Purpose ABC Dry Chemical

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120° F (-54°C to 49°C)



Brand	Product Code	Capacity	Chemical	Discharge Time	Range	ULC & ULC Rating
Strike-first	ABC-025VWD	2.5 lbs	ABC Dry	9 seconds	8-10 ft	1A: 10B : C
Strike-first	ABC-050WWD	5 lbs	ABC Dry	13 seconds	8-10 ft	3A: 10B : C
Strike-first	ABC-050WDDL	5 lbs	ABC Dry	9 seconds	8-10 ft	3A: 40B : C
Strike-first	ABC-100WWD	10 lbs	ABC Dry	9 seconds	10-15 ft	6A: 80B : C
Strike-first	ABC-200WWD	20 lbs	ABC Dry	9 seconds	10-15 ft	10A: 120B : C
Strike-first	ABC-300WWD	30 lbs	ABC Dry	9 seconds	10-15 ft	1A: 120B : C

Smart Solutions



MEETS OR EXCEEDS:
ANSI/UL 299 & 711



MEETS OR EXCEEDS:
CAN/ULC-S504 & S508



CLASS A

WOOD,
PAPER,
CLOTH



CLASS B

FLAMMABLE
LIQUIDS
& GASES



CLASS C

ELECTRICAL
CONDUCTIVITY



**6 YEAR
WARRANTY**